

JADE SUPERMATCH WHILE STOCKS LAST

Haier

2,5 kW

3,5 kW

MONOSPLIT



A+++ / A+++



Standard HR-HJ



PM 2.5
Detection



Self Clean



Precise
Dehumidification



Silence



Integrated
Wi-Fi Control



I Feel



3D



Eco Sensor



Puri Clean

- PM 2,5 detection
- Self-Clean
- Precise dehumidification
- Low noise level
- Integrated Wi-Fi control
- Easy installation
- 3D airflow: continuous movement of horizontal and vertical deflectors
- Eco Sensor
- Puri Clean

INDOOR UNIT	Model		AS25S2SJ1FA-3	AS35S2SJ1FA-3
OUTDOOR UNIT	Model		1U25MECFRA-3	1U35MECFRA-3
Performance data				
Output power - COOLING	nom (min-max)	kW	2,60 (1,00-4,00)	3,50 (1,00-4,00)
Output power - HEATING	nom (min-max)	kW	3,20 (1,10-5,40)	4,20 (1,30-5,80)
Absorbed power - COOLING	nom (min-max)	kW	0,577 (0,30-1,25)	0,795 (0,30-1,35)
Absorbed power - HEATING	nom (min-max)	kW	0,666 (0,30-1,85)	0,893 (0,30-1,85)
Energy class	EER	W/W	4,50	4,40
	COP	W/W	4,80	4,70
COOLING Pdesign	35 °C	kW	2,60	3,50
HEATING Pdesign	(-10 °C)	kW	2,60	2,65
Energy class	SEER		8,75 (A+++)	8,75 (A+++)
	SCOP		5,10 (A+++)	5,10 (A+++)
Annual Energy Consumption - COOLING		kWh/a	104	140
Annual Energy Consumption - HEATING		kWh/a	714	727
Indoor Unit				
Power supply		Ph/V/Hz	1/220-240/50	1/220-240/50
Treated air volume	H	m ³ /h	550	600
Dehumidification		L/h	1,2	1,6
High sound power - COOLING		dB	56	57
High sound power - HEATING		dB	56	57
Sound pressure - COOLING		dB(A)	36/32/29/15	37/33/30/16
Sound pressure - HEATING		dB(A)	36/32/29/15	37/33/30/16
Net dimensions	WxDxH	mm	923x215x320	923x215x320
Packaging dimensions	WxDxH	mm	1032x318x418	1032x318x418
Net/gross weight		kg	12,0/15,2	12,0/15,2
Outdoor Unit				
Power supply		Ph/V/Hz	1/220-240/50	1/220-240/50
Power cable		N x mm ²	3 x 1,5	3 x 1,5
Interconnection cable		N x mm ²	4 x 1,0	4 x 1,0
Sound power	H	dB	61	62
Sound pressure	H	dB(A)	48	49
Running current cooling/heating	Max	A	8,0/8,0	8,0/8,0
Starting current cooling/heating	Max	A	1,5/1,5	1,5/1,5
Net dimensions	WxDxH	mm	800x275x553	800x275x553
Packaging dimensions	WxDxH	mm	902x375x607	902x375x607
Net/gross weight		kg	29,8/33,6	29,8/33,6
Compressor type			Rotary Inverter	Rotary Inverter
Installation data				
Refrigerant			R32	R32
Liquid pipe	∅	mm (inch)	6,35 (1/4)	6,35 (1/4)
Gas pipe	∅	mm (inch)	9,52 (3/8)	9,52 (3/8)
Standard pipe length without refrigerant charge		m	7	7
Maximum pipe length		m	20	20
Maximum IU - OU elevation		m	10	10
Refrigerant charge in the factory		kg	0,74	0,74
Refrigerant charge in the factory		TCO ₂ eq	0,50	0,50
Additional ref. charge over std length		g/m	20	20
Operating limits - COOLING (in/out)	min-max	°C	21-35°C/-10-43°C	
Operating limits - HEATING (in/out)	min-max	°C	10-27°C/-20-24°C	

The data in this catalogue is purely indicative as the data may vary. Please be advised to check the accuracy of the data with the supplier before purchasing products.

Haierhvac.eu