

3S TANK NEW

Estimated Launch Date July 2024

Haier

94L

190L

MULTISPLIT



A



Integrated Wi-Fi Control



Easy Installation



Heat Recovery



AC & Domestic Hot Water

- Intergrated Wi-Fi Control
- Easy Installation
- Heat Recovery
- AC & Domestic Hot Water

Indoor Unit	Model		AN100S2ST1FA	AN200S2ST1FA
Performance data				
Volume		L	94	190
Max. water Outlet temp.		°C	55 °C (75 °C with electrical heater)	
Electric heater power		W	2,000	
COP average Climate			2,2/ 2,3	2,4/ 2,5
COP warmer Climate			2.7	2.8
Seasonal Efficiency			M	L
Energy Class	EN16147(2017)		A	
Heating Time average Climate		h:mm	2:20/ 2:30	3:10/ 3:20
Heating Time warm Climate		h:mm	2:00/ 2:10	2:50/ 3:00
Power supply		Ph/V/Hz	1/220~240/50/60	
Interconnection cable		N x mm2	2*0.75	
Indoor Unit				
Net dimensions	WxDxH	mm	470x560x1110	520x610x1650
Packaging dimensions	WxDxH	mm	730x730x1285	730x730x1825
Net	(gross weight)	kg	45,0 (62,0)	70,0 (88,0)
Material			Enamel	
Installation data				
Liquid pipe	Ø	mm	6,35 (1/4)	6,35 (1/4)
Gas pipe	Ø	mm	9,52 (3/8)	9,52 (3/8)
Control				
Standard			Integrated	

AN100S2ST1FA

AN200S2ST1FA

